

MULTIFLEX 600

highly flexible, oil resistant, open installation TC-ER, PLTC-ER, NFPA 79



HELUKABEL MULTIFLEX 600 P/N 63136 14AWG 4C (UL) TC-ER 90°C DRY 75°C WET 600 V SUN RES DIR BUR OIL RES I/II E330430 OR MTW "HIGH FLEXIBLE" OR WTTC 1000 V OR c(UL)CIC TC FT4 LL257839 CSA AWM I/II 90°C 600 V FT4 CE ROHS

Technical data

- Highly flexible PVC control cable acc. to UL Std. 1277
- **Temperature range**
flexing -5°C to +90°C
fixed installation -40°C to +90°C
- **Nominal voltage**
TC 600 V
WTTC 1000 V
- **Test voltage**
3000 V
- **Minimum bending radius**
flexing 7,5x cable Ø
- **Insulation resistance**
min. 20 MOhm x km
- **Radiation resistance**
up to 80x10⁶ cJ/kg (up to 80 Mrad)

Cable structure

- Bare copper conductor, extra fine wire stranded, with AWG dimensions
- Core insulation of special PVC with transparent nylon skin
- Core identification to DIN VDE 0293 black cores with continuous white numbering
- GN-YE conductor, 3 cores and above in the outer layer
- Cores stranded in layers with optimal lay length
- Separator
- Outer sheath of special PVC
- Sheath colour: black (RAL 9005)
- With length marking in feet

Properties

- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers
- UV resistant
- **Tests**
- Self-extinguishing and flame retardant acc. to CSA FT4
- **UL:**
TC-ER, PLTC-ER (AWG 18 - AWG 12), ITC-ER (AWG 18 - AWG 12), MTW, NFPA 79, WTTC 1000 V, DP-1, OIL RES I&II, 90°C dry / 75°C wet, Class 1 Div. 2 per NEC Art 336, 392, 501, crush impact test acc. to UL 1277
- **CSA:**
c(UL) CIC-TC FT4, CSA AWM I/II A/B FT4

Note

Advantages

- Highly flexible, simple installation

Available on request

- With blue cores (DC)
- With red cores (AC)
- Grey or TPE outer sheath

Application

HELUKABEL® MULTIFLEX 600 is a highly flexible, oil resistant control cable. The special combination of TC-ER, PLTC-ER and ITC-ER allows this cable to be used as a connecting cable for industrial plant and machinery in accordance with NFPA 79. Approved for open, unprotected installation in cable trays to the machine. Its outstanding oil resistance (OIL RES I & II) guarantees a long service life; for industrial applications in dry, damp and wet environments. Recommended applications: production lines, bottling plants, machine construction, switch cabinets, conveyor systems, packaging machines, automotive industry. Please observe applicable installation regulations for use in energy supply chains.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	No. cores x cross-sec. mm ²	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
62502	2 x 0,5	20	6,9	10,0	53,0
62503	3 G 0,5	20	7,3	14,0	61,0
62504	4 G 0,5	20	8,0	19,0	72,0
62505	5 G 0,5	20	8,6	24,0	85,0
62506	7 G 0,5	20	9,9	34,0	110,0
62507	12 G 0,5	20	11,4	58,0	158,0
62508	18 G 0,5	20	14,2	86,0	241,0
62509	25 G 0,5	20	17,0	120,0	316,0
62510	34 G 0,5	20	18,9	163,0	439,0
62511	3 G 0,75	18	7,8	22,0	75,0
62512	4 G 0,75	18	8,6	29,0	91,0
62513	5 G 0,75	18	9,3	36,0	103,0
62514	7 G 0,75	18	10,8	50,0	136,0
62515	12 G 0,75	18	12,4	86,0	228,0
62516	15 G 0,75	18	13,8	108,0	273,0
62517	18 G 0,75	18	15,4	130,0	311,0
62518	25 G 0,75	18	18,5	180,0	498,0
62519	34 G 0,75	18	20,5	245,0	550,0
62520	36 G 0,75	18	20,6	259,0	570,0
62521	42 G 0,75	18	22,3	302,0	600,0
62522	3 G 1,5	16	8,6	43,0	100,0
62523	4 G 1,5	16	9,5	58,0	122,0
62524	5 G 1,5	16	10,3	72,0	148,0
62525	7 G 1,5	16	12,0	101,0	197,0
62526	9 G 1,5	16	14,2	130,0	244,0
62527	12 G 1,5	16	14,7	173,0	328,0
62528	18 G 1,5	16	17,2	259,0	459,0

Part no.	No. cores x cross-sec. mm ²	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
62529	25 G 1,5	16	20,8	360,0	665,0
62530	34 G 1,5	16	23,0	490,0	1084,0
62531	41 G 1,5	16	25,1	590,0	1260,0
62532	50 G 1,5	16	27,7	720,0	1521,0
62533	60 G 1,5	16	29,5	864,0	1885,0
62534	3 G 2,5	14	9,8	72,0	160,0
63136	4 G 2,5	14	10,6	96,0	173,0
62535	5 G 2,5	14	11,9	120,0	268,0
62536	7 G 2,5	14	13,6	168,0	307,0
62537	9 G 2,5	14	16,1	216,0	437,0
62538	12 G 2,5	14	16,9	288,0	572,0
62539	18 G 2,5	14	20,1	432,0	800,0
62540	25 G 2,5	14	25,1	600,0	1100,0
62541	3 G 4	12	11,3	115,0	221,0
62542	4 G 4	12	12,4	154,0	247,0
62543	5 G 4	12	13,8	192,0	318,0
62544	7 G 4	12	16,9	269,0	438,0
62545	4 G 6	10	15,3	230,0	383,0
62546	5 G 6	10	16,6	288,0	481,0
62547	7 G 6	10	18,2	403,0	800,0
62548	4 G 10	8	19,7	384,0	671,0
62549	5 G 10	8	22,0	480,0	990,0
62550	4 G 16	6	23,7	614,0	951,0
62551	5 G 16	6	26,1	768,0	1500,0
62552	4 G 25	4	34,0	960,0	1700,0
62554	4 G 35	2	37,0	1344,0	2300,0

Dimensions and specifications may be changed without prior notice. (RN01)